

Heracleum Endless

BERTJAN POT | POWERED THROUGH ELECTROSANDWICH® BY MARCEL WANDERS



A perpetual blossom of new branches that multiplies by the meter, Heracleum Endless by Bertjan Pot may really grow out of reach! There is hardly a limit to what Heracleum can now achieve by developing in straight lines, generating corners and forming square geometric shapes. The sparkling glamour of its LED leafs and the festivity of its foliage design can potentially decorate the perimeter of an entire room or hang above your dining table in its exact same shape. Given the seed of a good idea, it may grow into any kind of environment, meter by meter. Let there be no end to the bloom of Heracleum Endless!

Detailing



Heracleum is powered by Electrosandwich, a technique of coating conductive layers, very thin and delicate. A design not possible with normal wires.

Colours




Copper



Nickel

Heracleum Endless

Dimensions



Product

WIDTH 116cm | 45.7"
HEIGHT 37cm | 14.6"
DEPTH 57cm | 22.4"
WEIGHT NETTO 4.5kg | 9.92lbs

Packaging

WIDTH 72cm | 28.3"
HEIGHT 53cm | 20.9"
CUBAGE 0.6m³ | 21.02ft³
LENGTH 156cm | 61.4"
WEIGHT 6.5cm | 14.33lbs

Technical CE

MATERIAL

Metal wire frame, polycarbonate lenses, ultra thin suspension wire

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

45

INPUT VOLTAGE

200-265

MAX POWER CONSUMPTION

15W

LAMPHOLDER

LED (Solid state)

COLOUR

Transparent with tinned cores

CANOPY

Pebble II Copper Coated, ABS

CRI

80

LIGHT OUTPUT

400 lm

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

DIMMABLE

Yes

LIFETIME

20000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATUE

2700 K

LIGHT DIRECTION

All directions

CONSTANT CURRENT / CONSTANT VOLTAGE

Constant voltage

EEI

0.4

MEASURED POWER CONSUMPTION

13.34W

POWERSUPPLY TYPE

Electronic Low Voltage (ELV)

EFFICIENCY

26.67 lm/W

DRIVER TYPE

Moooli Elita One Driver

*Technical cULus***MATERIAL**

Metal wire frame, polycarbonate lenses, ultra thin suspension wire

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

45

SHAPE

Linear

INPUT VOLTAGE

110-127

FREQUENCY

50/60

MAX POWER CONSUMPTION

12W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

20000 hours

COLOUR

Transparent with tinned cores

CABLE LENGTH

400cm | 157.5"

CANOPY

Pebble II Copper Coated, ABS

COLOUR TEMPERATURE

2700 K

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

400 lm

CONSTANT CURRENT / CONSTANT VOLTAGE

Constant voltage

EEI

0.32

EFFICIENCY

33.33 lm/W

DRIVER TYPE


Moooli Elita One Driver

POWERSUPPLY TYPE

Electronic Low Voltage (ELV)

Heracleum Endless Heracleum Endless Bend 135

Dimensions



Product

WIDTH 12,5cm | 4.9"

HEIGHT 1cm | 0.4"

DEPTH 5,9cm | 2.3"

Packaging

WIDTH 6cm | 2.4"

HEIGHT 2cm | 0.8"


CUBAGE 0m³ | 0.01ft³

LENGTH 12,5cm | 4.9"

WEIGHT 0,3cm | 0.66lbs

Heracleum Endless Heracleum Endless Bend 90

Dimensions



Product

WIDTH 12,5cm | 4.9"

HEIGHT 1cm | 0.4"

DEPTH 12,5cm | 4.9"

Packaging

WIDTH 12,5cm | 4.9"

HEIGHT 2cm | 0.8"

CUBAGE 0m³ | 0.01ft³

LENGTH 12,5cm | 4.9"

WEIGHT 0,3cm | 0.66lbs

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

DIMMER TYPE

Mains and/or 1-10V dimmable (trailing edge / reverse phase)

LOAD TYPE

Capacitive load (C-Type)